



# **RFID Eight-channel Fixed Reader CER501**

CER501 is a powerful 8-channel UHF RFID reader designed for high-efficiency, multi-tag environments. Engineered with the advanced IMPINJ E710/E510/E310 reader, it delivers exceptional performance and compatibility with EPC Global C1 Gen 2 and ISO 18000-6C tags. Supporting up to eight external antennas, the CER501 is perfectly suited for demanding applications in logistics, access control, fashion retail, warehousing, brand protection, and smart manufacturing.



#### **Features**

- Embedded Linux operating system paired with advanced middleware for edge computing, significantly reducing system complexity and simplifying deployment and maintenance.
- Superior multi-tag reading capabilities, delivers exceptional multi-tag reading accuracy, supporting dense tag environments, large-scale data write/read operations, and real-time signal strength (RSSI) detection.
- Robust network adaptability, supports for multiple communication protocols. Compatible with Web Service development for seamless integration and easy large-scale deployment.

#### **Physical Specification**

Dimension (mm)	215(L)*158(W)*38(H) (±1)
Weight (kg)	1.27 (±0.01)
Housing Materials	Gray sheet metal
Antenna Interface	SMA (External thread inside hole)
Operating Temperature	-20∼+55 °C
Storage Temperature	-20∼+85 °C
Environment Humidity	5% to 95%RH, no condensation







# **Technical Specification**

RFID Protocol	EPC global Class1 Gen 2/ISO 18000-6C
Operating System	Linux
Frequency	865~868MHz/902~928MHz (adjustable by country or region)
Chip	IMPINJ E710/E510/E310
Receiver Sensitivity	E710: -87dBm; E510: -81dBm; E310: -74dBm
Frequency Hopping Technique	Broad-spectrum frequency hopping (FHSS) or fixed-frequency transmission mode
RFID Power	0dBm-33dBm adjustable, +/-1.0dBm
RFID Read Range	E710: Range > 13m (compatible with 9DB antenna and tag 9662); E510: Range > 11m (compatible with 9DB antenna and tag 9662); E310: Range > 10m (compatible with 9DB antenna and tag 9662);
RFID Read Speed	E710: Maximum label reading speed >900pcs/s; E510: Maximum label reading speed >600pcs/s; E310: Maximum label reading speed >350pcs/s;
Tag Buffer	>10W pcs @ 96bit EPC
RSSI Strength Detection	Support
Automatic Antenna Detection	Support
Reader Operating Mode	Master/slave mode, single-machine mode, or trigger mode
Power Supply	Power adapter: AC input 100~240V/50-60Hz, DC output 12V/4A; DC power supply: 12V to 24V/4A, POE optional
Power	5W~24W
GPIO	3 inputs, 3 outputs; (4 inputs, 8 outputs optional)
Communication Protocol	RS-232, TCP/IP, Modbus, HTTP/HTTPS, MQTT, RabbitMQ
Hardware Interface	RS232, RJ45
Programming Language	C#, JAVA
Development Environment	Linux, Android, Windows, PLC, Web





## **Package Information**

Package Size (mm)	317(L)*255(W)*66(H) (±3)
Package Weight (kg)	1.83 (±0.01)

#### **GPIO Definition**

Below is the definition for 3 input and 3 output channels.

GPO1	Output Voltage: Same as DC adapter Max Output Current: 500 mA
GPO2	Output Voltage: Same as DC adapter Max Output Current: 500 mA
GPO3	Output Voltage: Same as DC adapter Max Output Current: 500 mA
GND	Ground connection
GND	Ground connection
GPI1+	Input voltage range: 9~24V
GPI1-	Common ground with trigger source
GPI2+	Input voltage range: 9~24V
GPI2-	Common ground with trigger source
GPI3+	Input voltage range: 9~24V
GPI3-	Common ground with trigger source
VCC	Can provide the same voltage as the DC power adapter
GND	Ground connection
NC	Reserve

## **Product Dimension (mm)**



Hangzhou Century Co., Ltd 528 Xingqi Road, Linping Area, Hangzhou, P.R.China 311106 +86 571 28818756 info@century-cn.com www.century-cn.com





aaaaaaaaaaaaaa

6P01 3P02 6ND 6ND 6ND -11+ 212+



